

advanced



**HiPerFRED<sup>2</sup>**

High Performance Fast Recovery Diode  
Low Loss and Soft Recovery  
Single Diode

$$\begin{aligned} V_{RRM} &= 400 \text{ V} \\ I_{FAV} &= 15 \text{ A} \\ t_{rr} &= 45 \text{ ns} \end{aligned}$$

Part number

DPG 15 I 400PM



Backside: isolated

**Features / Advantages:**

- Planar passivated chips
- Very low leakage current
- Very short recovery time
- Improved thermal behaviour
- Very low  $I_{RM}$ -values
- Very soft recovery behaviour
- Avalanche voltage rated for reliable operation
- Soft reverse recovery for low EMI/RFI
- Low  $I_{RM}$  reduces:
  - Power dissipation within the diode
  - Turn-on loss in the commutating switch

**Applications:**

- Antiparallel diode for high frequency switching devices
- Antisaturation diode
- Snubber diode
- Free wheeling diode
- Rectifiers in switch mode power supplies (SMPS)
- Uninterruptible power supplies (UPS)

**Package:**

- TO-220FPAC
- Industry standard outline
  - Plastic overmolded tab for electrical isolation
  - Epoxy meets UL 94V-0
  - RoHS compliant


**Ratings**

Symbol	Definition	Conditions	Ratings			Unit	
			min.	typ.	max.		
$V_{RRM}$	max. repetitive reverse voltage	$T_{VJ} = 25\text{ °C}$			400	V	
$I_R$	reverse current	$V_R = 400\text{ V}$			1	$\mu\text{A}$	
		$V_R = 400\text{ V}$			0.1	mA	
$V_F$	forward voltage	$I_F = 15\text{ A}$			1.40	V	
		$I_F = 30\text{ A}$		0.00	1.60	V	
		$I_F = 15\text{ A}$	$T_{VJ} = 150\text{ °C}$			1.08	V
		$I_F = 30\text{ A}$	$T_{VJ} = 150\text{ °C}$		0.00	1.29	V
$I_{FAV}$	average forward current	rectangular, $d = 0.5$			15	A	
$V_{FO}$	threshold voltage	} for power loss calculation only			0.75	V	
$r_F$	slope resistance				20.4	m $\Omega$	
$R_{thJC}$	thermal resistance junction to case				4.20	K/W	
$T_{VJ}$	virtual junction temperature		-55		175	$^{\circ}\text{C}$	
$P_{tot}$	total power dissipation	$T_C = 25\text{ °C}$			36	W	
$I_{FSM}$	max. forward surge current	$t_p = 10\text{ ms (50 Hz), sine}$			130	A	
$I_{RM}$	max. reverse recovery current	$I_F = 15\text{ A};$		4		A	
		$-di_F/dt = 200\text{ A}/\mu\text{s}$	$T_{VJ} = 125\text{ °C}$			A	
$t_{rr}$	reverse recovery time	$V_R = 100\text{ V}$	$T_{VJ} = 25\text{ °C}$	45		ns	
			$T_{VJ} = 125\text{ °C}$			ns	
$C_J$	junction capacitance	$V_R = 200\text{ V}; f = 1\text{ MHz}$	$T_{VJ} = 25\text{ °C}$	tbd		pF	
$E_{AS}$	non-repetitive avalanche energy	$I_{AS} = \text{tbd A}; L = 100\text{ }\mu\text{H}$	$T_{VJ} = 25\text{ °C}$		tbd	mJ	
$I_{AR}$	repetitive avalanche current	$V_A = 1.5 \cdot V_R$ typ.; $f = 10\text{ kHz}$			tbd	A	

Symbol	Definition	Conditions	Ratings			Unit
			min.	typ.	max.	
$I_{RMS}$	RMS current	per pin*			35	A
$R_{thCH}$	thermal resistance case to heatsink			0.50		K/W
$M_D$	mounting torque		0.4		0.6	Nm
$F_C$	mounting force with clip		20		60	N
$T_{sta}$	storage temperature		-55		150	°C
<b>Weight</b>				2		g

\* Irms is typically limited by: 1. pin-to-chip resistance; or by 2. current capability of the chip.

In case of 1, a common cathode/anode configuration and a non-isolated backside, the whole current capability can be used by connecting the backside.

**Outlines TO-220FPAC**


SYM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.177	.193	4.50	4.90
A1	.092	.108	2.34	2.74
A2	.101	.117	2.56	2.96
b	.028	.035	0.70	0.90
b1	.050	.058	1.27	1.47
c	.018	.024	0.45	0.60
D	.617	.633	15.67	16.07
d1	0	.043	0	1.10
E	.392	.408	9.96	10.36
e	.100 BSC		2.54 BSC	
H	.255	.271	6.48	6.88
L	.499	.523	12.68	13.28
L1	.119	.135	3.03	3.43
ØP	.121	.129	3.08	3.28
Q	.126	.134	3.20	3.40

**NOTE:**

1. All metal surface are matte pure tin plated except trimmed area.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[IXYS:](#)

[DPG15I400PM](#)