

# NTD110N02R, STD110N02R

## Power MOSFET

### 24 V, 110 A, N-Channel DPAK

#### Features

- Planar HD3e Process for Fast Switching Performance
- Low  $R_{DS(on)}$  to Minimize Conduction Loss
- Low  $C_{iss}$  to Minimize Driver Loss
- Low Gate Charge
- Optimized for High Side Switching Requirements in High-Efficiency DC-DC Converters
- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free and are RoHS Compliant

#### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

Rating	Symbol	Value	Unit
Drain-to-Source Voltage	$V_{DSS}$	24	V
Gate-to-Source Voltage – Continuous	$V_{GS}$	$\pm 20$	V
Thermal Resistance – Junction-to-Case	$R_{\theta JC}$	1.35	$^\circ\text{C/W}$
Total Power Dissipation @ $T_C = 25^\circ\text{C}$	$P_D$	110	W
Drain Current	$I_D$	110	A
– Continuous @ $T_C = 25^\circ\text{C}$ , Chip	$I_D$	110	A
– Continuous @ $T_C = 25^\circ\text{C}$	$I_D$	110	A
Limited by Package	$I_D$	32	A
– Continuous @ $T_A = 25^\circ\text{C}$	$I_D$	32	A
Limited by Wires	$I_D$	110	A
– Single Pulse ( $t_p = 10 \mu\text{s}$ )	$I_D$	110	A
Thermal Resistance	$R_{\theta JA}$	52	$^\circ\text{C/W}$
– Junction-to-Ambient (Note 1)	$R_{\theta JA}$	52	$^\circ\text{C/W}$
– Total Power Dissipation @ $T_A = 25^\circ\text{C}$	$P_D$	2.88	W
– Drain Current – Continuous @ $T_A = 25^\circ\text{C}$	$I_D$	17.5	A
Thermal Resistance	$R_{\theta JA}$	100	$^\circ\text{C/W}$
– Junction-to-Ambient (Note 2)	$R_{\theta JA}$	100	$^\circ\text{C/W}$
– Total Power Dissipation @ $T_A = 25^\circ\text{C}$	$P_D$	1.5	W
– Drain Current – Continuous @ $T_A = 25^\circ\text{C}$	$I_D$	12.5	A
Operating and Storage Temperature Range	$T_J, T_{stg}$	-55 to 175	$^\circ\text{C}$
Single Pulse Drain-to-Source Avalanche Energy – Starting $T_J = 25^\circ\text{C}$ ( $V_{DD} = 50 \text{ Vdc}$ , $V_{GS} = 10 \text{ Vdc}$ , $I_L = 15.5 \text{ Apk}$ , $L = 1.0 \text{ mH}$ , $R_G = 25 \Omega$ )	$E_{AS}$	120	mJ
Maximum Lead Temperature for Soldering Purposes, (1/8" from case for 10 s)	$T_L$	260	$^\circ\text{C}$

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.



1. When surface mounted to an FR4 board using 0.5 sq in drain pad size.
2. When surface mounted to an FR4 board using the minimum recommended pad size.



ON Semiconductor®


<http://onsemi.com>

$V_{(BR)DSS}$	$R_{DS(on)}$ TYP	$I_D$ MAX
24 V	4.1 m $\Omega$ @ 10 V	110 A



**DPAK  
CASE 369AA  
(Surface Mount)  
STYLE 2**

#### MARKING DIAGRAM & PIN ASSIGNMENT



- A = Assembly Location\*
- Y = Year
- WW = Work Week
- T110N2 = Device Code
- G = Pb-Free Package

\* The Assembly Location code (A) is front side optional. In cases where the Assembly Location is stamped in the package, the front side assembly code may be blank.

#### ORDERING INFORMATION

See detailed ordering and shipping information on page 5 of this data sheet.

# NTD110N02R, STD110N02R

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
<b>OFF CHARACTERISTICS</b>					
Drain-to-Source Breakdown Voltage (Note 3) ( $V_{GS} = 0\text{ V}$ , $I_D = 250\ \mu\text{A}$ )	$V_{(BR)DSS}$	24	28		V
Positive Temperature Coefficient			15		mV/ $^\circ\text{C}$
Zero Gate Voltage Drain Current ( $V_{DS} = 20\text{ V}$ , $V_{GS} = 0\text{ V}$ ) ( $V_{DS} = 20\text{ V}$ , $V_{GS} = 0\text{ V}$ , $T_J = 125^\circ\text{C}$ )	$I_{DSS}$			1.5 10	$\mu\text{A}$
Gate-Body Leakage Current ( $V_{GS} = \pm 20\text{ V}$ , $V_{DS} = 0\text{ V}$ )	$I_{GSS}$			$\pm 100$	nA

## ON CHARACTERISTICS (Note 3)

Gate Threshold Voltage (Note 3) ( $V_{DS} = V_{GS}$ , $I_D = 250\ \mu\text{A}$ )	$V_{GS(th)}$	1.0	1.5 5.0	2.0	V mV/ $^\circ\text{C}$
Negative Threshold Temperature Coefficient					
Static Drain-to-Source On-Resistance (Note 3) ( $V_{GS} = 10\text{ V}$ , $I_D = 110\text{ A}$ ) ( $V_{GS} = 4.5\text{ V}$ , $I_D = 55\text{ A}$ ) ( $V_{GS} = 10\text{ V}$ , $I_D = 20\text{ A}$ ) ( $V_{GS} = 4.5\text{ V}$ , $I_D = 20\text{ A}$ )	$R_{DS(on)}$		4.1 5.5 3.9 5.5	4.6 6.2	m $\Omega$
Forward Transconductance ( $V_{DS} = 10\text{ V}$ , $I_D = 15\text{ A}$ ) (Note 3)	$g_{FS}$		44		Mhos

## DYNAMIC CHARACTERISTICS

Input Capacitance	$(V_{DS} = 20\text{ V}$ , $V_{GS} = 0\text{ V}$ , $f = 1.0\text{ MHz}$ )	$C_{iss}$	2710	3440	pF
Output Capacitance		$C_{oss}$	1105	1670	
Transfer Capacitance		$C_{rss}$	450	640	

## SWITCHING CHARACTERISTICS (Note 4)

Turn-On Delay Time	$(V_{GS} = 10\text{ V}$ , $V_{DD} = 10\text{ V}$ , $I_D = 40\text{ A}$ , $R_G = 3.0\ \Omega$ )	$t_{d(on)}$	11	22	ns
Rise Time		$t_r$	39	80	
Turn-Off Delay Time		$t_{d(off)}$	27	40	
Fall Time		$t_f$	21	40	
Gate Charge	$(V_{GS} = 4.5\text{ V}$ , $I_D = 40\text{ A}$ , $V_{DS} = 10\text{ V}$ ) (Note 3)	$Q_T$	23.6	28	nC
		$Q_{GS}$	5.1		
		$Q_{GD}$	11		

## SOURCE-DRAIN DIODE CHARACTERISTICS

Forward On-Voltage	$(I_S = 20\text{ A}$ , $V_{GS} = 0\text{ V}$ ) (Note 3) $(I_S = 55\text{ A}$ , $V_{GS} = 0\text{ V}$ ) $(I_S = 20\text{ A}$ , $V_{GS} = 0\text{ V}$ , $T_J = 125^\circ\text{C}$ )	$V_{SD}$	0.82 0.99 0.65	1.2	V
Reverse Recovery Time	$(I_S = 30\text{ A}$ , $V_{GS} = 0\text{ V}$ , $di_S/dt = 100\text{ A}/\mu\text{s}$ ) (Note 3)	$t_{rr}$	36.5		ns
		$t_a$	30		
		$t_b$	25		
Reverse Recovery Stored Charge		$Q_{rr}$	0.048		$\mu\text{C}$

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Pulse Test: Pulse Width  $\leq 300\ \mu\text{s}$ , Duty Cycle  $\leq 2\%$ .

4. Switching characteristics are independent of operating junction temperatures.

# NTD110N02R, STD110N02R




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance versus Gate-to-Source Voltage




Figure 4. On-Resistance versus Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature






Figure 6. Drain-to-Source Leakage Current versus Voltage


# NTD110N02R, STD110N02R




**Figure 7. Capacitance Variation**




**Figure 8. Gate-to-Source and Drain-to-Source Voltage versus Total Charge**



**Figure 9. Resistive Switching Time Variation versus Gate Resistance**




**Figure 10. Diode Forward Voltage versus Current**



**Figure 11. Maximum Rated Forward Biased Safe Operating Area**

# NTD110N02R, STD110N02R



**Figure 12. Thermal Response**

## ORDERING INFORMATION

Device	Package	Shipping <sup>†</sup>
NTD110N02RT4G	DPAK (Pb-Free)	2500 / Tape & Reel
STD110N02RT4G*	DPAK (Pb-Free)	2500 / Tape & Reel


<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable.

# NTD110N02R, STD110N02R

## PACKAGE DIMENSIONS


### DPAK (SINGLE GUAGE) CASE 369AA ISSUE B



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
  2. CONTROLLING DIMENSION: INCHES.
  3. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS b3, L3 and Z.
  4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.006 INCHES PER SIDE.
  5. DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
  6. DATUMS A AND B ARE DETERMINED AT DATUM PLANE H.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.086	0.094	2.18	2.38
A1	0.000	0.005	0.00	0.13
b	0.025	0.035	0.63	0.89
b2	0.030	0.045	0.76	1.14
b3	0.180	0.215	4.57	5.46
c	0.018	0.024	0.46	0.61
c2	0.018	0.024	0.46	0.61
D	0.235	0.245	5.97	6.22
E	0.250	0.265	6.35	6.73
e	0.090 BSC		2.29 BSC	
H	0.370	0.410	9.40	10.41
L	0.055	0.070	1.40	1.78
L1	0.108 REF		2.74 REF	
L2	0.020 BSC		0.51 BSC	
L3	0.035	0.050	0.89	1.27
L4	---	0.040	---	1.01
Z	0.155	---	3.93	---

### SOLDERING FOOTPRINT\*



SCALE 3:1  $\left(\frac{\text{mm}}{\text{inches}}\right)$

- STYLE 2:  
PIN 1. GATE  
2. DRAIN  
3. SOURCE  
4. DRAIN

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and the are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor:](#)

[NTD110N02RT4G](#)